Thermo Flex PLUS

The most trusted name in the industry!

CONFIDENCE IN TEXTILES

Tested for harmful substances according to Deko-Tex® Standard 100 00000000

- Widest color selection in the industry
- Beautiful screen-print like finish and soft touch
- Most colors can be layered for an even more colorful visual experience
- Pressure-sensitive carrier makes for an easy weeding experience
- When applied correctly, Plus will outlast the life of the garment

Acceptable Fabrics

Cotton, Uncoated Polyester, Cotton/Polyester Blends, Polyester/Acrylic Blends, Linen, Wool. Excluding Nylon

Sizing Available

Available Widths (in.): 12", 15", 20", and 30" Available Lengths (ft.): 15', 30', 45', 60', 90' and 150' rolls 150' rolls may not be available in some colors Sheets Available in Matte Colors only: 12"x15"



Thickness

Matte, Metallic, and Glossy: 4 mils/100 microns Metal Flakes: 5 mils/125 microns

Special Precautions

* Columbia Blue, Metallics, Metal Flakes, and Neon colors cannot be layered beneath anything.

COLOR VARIATION: During the manufacturing process, sometimes there is a slight color variation between rolls. This is especially true for neon colors.





45° Blade Recommended



Cut this material in mirror image



320°F - 330°F



Medium, even pressure



15 Seconds



Peel warm (Except Neon and Columbia Blue - Peel Cold), cover with Teflon & repress for 2 seconds.



Wash warm, tumble dry normal. Suitable for dry-cleaning.



Tech Support: 877.437.8556 | SpecialtyMaterials.com

Copyright © 2020, Specialty Materials & Digital Decoration, LLC. All rights reserved. Tulsa, OK 74107 | 877-437-8556

Specialty Materials

All technical information and recommendations are based on tests we believe to be reliable. However, we cannot guarantee performance for conditions not under manufacturer's control. Before using, please determine the suitability of product for its intended use. The user assumes all risk and liability whatsoever in connection with the use of this product. Seller's and manufacturer's only obligation shall be to replace such quantity of the product proved to be defective by manufacturer. Test on dazzle cloth and other moisture-wicking polyesters. Moisture-wicking materials have better adhesion when washed and dried using no fabric softener or blotted with rubbing alcohol before pressing. Be advised that dye migration has occurred with low energy dyes in polyester and poly-blend fabrics.









Copyright © 2020, Specialty Materials & Digital Decoration, LLC. All rights reserved.