

IColor 2-Step *Select* Transfer Media Instructions

Part # ICHTSELA4/V2(8.27" x 11.69") (210mm x 297mm)

Part # ICHTSELA3 (11.7" x 16.5") (297mm x 420 mm)

Part # ICHTSELA4XL (8.27" x 17") (210mm x 432 mm)

Temperature	Time	Paper Setting	Pressure
310°F / 154°C	120 / 30 Seconds	iColor 500/600: Transparency iColor 550/540: Coated Glossy iColor 800: Thick to 300g	8

The IColor 2-Step Select Transfer Media set will allow you to transfer prints from the IColor series of printers (including white and fluorescent color prints) onto a variety of garments, especially dark fabrics. The translucent adhesive applied as a result of the 2-step process increases the adhesion to your garment for increased durability, and stretchability on your finished product. Rasterization and breathability integrated into your design, as well as using the garment color as a mask, will enhance the stretch limit and softness of your finished product.

IColor 2-Step Select Transfer Media works at a higher temperature as compared to the IColor Premium paper (310°F / 154°C), so some care must be taken when pressing onto some types of synthetic material such as nylon or polyester. Spandex or Lycra material is not recommended at this temperature. This media has several advantages which complements UNINET's robust line of transfer media. It has a matte texture instead of a shiny finish, and has a very strong adhesive which helps prevent images from pulling apart. This lower cost media is a great everyday choice for textile transfers.

IColor 2-Step Select Transfer Media is a weed-free system, ensuring little time is wasted picking and weeding your transfer prints, enabling you to produce detailed, high quality images while dramatically reducing your production time.

Finished garments will last between 30 - 50 washes depending on how it's laundered. It is recommended to wash finished garments inside out in cold or warm water and low agitation. Avoid fabric softener. Tumble dry on low setting - For best results, hang to dry. If ironing is necessary, you must place a piece of kraft paper between the pressed image and the hot iron. Failure to do this will result in a melted transfer.

Designed to work with the IColor series of specialty printers, the IColor 2-Step Select Transfer Media will also work with many popular color laser printers - please check with your printer manufacturer for compatibility. White toner enabled printers are highly suggested for best results.

IColor 2-Step Select Transfer Media is used as a set, comprising of a 'Transparent Transfer Sheet' and an 'Adhesive Sheet'. Note that these are sold as a set and cannot be sold individually.

INSTRUCTIONS FOR BEST RESULTS:

1. Place the transparent transfer sheet into the appropriate tray of the IColor printer.



The coated, rough side is the print side.

- IColor 500 / 600: Print side face up in Multipurpose Tray
- IColor 550 / 540 / 800: Print side face down in the Multipurpose Tray

To avoid printer jams, stack a few sheets in the tray at once so the printer pulls the media cleanly.

2. Printer Settings:

In the RIP software settings, choose the paper type according to the printer being used. Make sure you are working within the overprint queue in the ProRIP software or 'B' Configuration if using the TransferRIP software.

- IColor 500 / 600: Set media type to 'Transparency'; and media weight to 'Ultra Heavy 1'
- IColor 550 / 540: Set paper type to 'Coated Glossy'
- IColor 800: Set paper type to 'Thick to 300g' (Thick to 220g can be used for low coverage graphics without black print)



Specific print modes and sizes for this media are available when using the IColor ProRIP software.



The page size should match the size of the media being used (A4, A4 XL, A3).



Remember to set the job to **mirror print**, ensuring the correct orientation when transferred to the textile. White overprint should be set to 225% for the IColor 550/540, 300% for all other models.

NOTE FOR IColor 550/540 ONLY: For a brighter or more vibrant image, use the Ultra Bright Version. If not, you can print on the adhesive sheet, but do so at your own risk. UNINET does not cover fuser damage if a jam occurs, so pay particular attention to the print settings. See the Tech Tips section on 'increasing brightness' and 'increasing vibrancy' for more details.

3. Print the image.

4. Preheat the press to 310°F / 154°C and keep the press closed for at least 5 minutes before proceeding to heat up the lower platen.

- This step is extremely important to ensure a good bond during the marrying process. Do not proceed until you feel the heat radiating from the bottom of the press platen, or you may experience incomplete transfers.

5. Place the printed image in the middle of the press with the printed side facing up. Place the adhesive sheet on top of the print, adhesive coated side down – the image and the adhesive should be face-to-face.



Adhesive side is the smooth, coated side

- **TIP:** Fold a small corner of the adhesive sheet over, prior to pressing (this will make it easier to peel apart after pressing).

6. Cover the media with kraft paper or a Teflon sheet and press the two sheets together in the heat press at 310°F / 154°C for 120 seconds with medium high pressure.

7. Open the press and immediately (while hot) - rub the media with a piece of textile for 5 seconds, then peel the adhesive sheet away from the transparent transfer sheet diagonally in one slow, low and fluid motion.

- This must be done with the sheets on the press to minimize heat loss. The use of heat resistant gloves will help keep the media in place due to the temperature of the lower platen.
- **TIP:** In order to avoid a faulty peel, it is recommended to peel from the side of the image with the greatest toner density.
- **TIP:** For images with a lot of black print (especially when printing with the IColor 800W), it may be necessary to press for a longer period of time and increase the dwell time in order to achieve a clean adhesive pull.
- **TIP: Slow down at the end of the peel and allow the adhesive sheet to 'fall off' to ensure that you do not lose the last edge of the graphic.**

8. Observe the used adhesive sheet – you will see the adhesive was removed only where toner was present on the transfer sheet.

- If you see any part of your design on the adhesive sheet, you did not get a clean pull. See Tech Tips for reasons why this may have happened.
- Examine the transfer sheet to determine if the transfer is acceptable and proceed to Step 9. Discard the used adhesive sheet.

9. Trim off the edges of the transparent transfer sheet using a pair of scissors or a cutting board. This will ensure no excess adhesive sticks to the garment and eliminate the chance of a white box around your design.

10. Place or thread your garment on the press. Position the transfer sheet (print side down) onto the garment.

- It is suggested that you use heat resistant tape to secure the sheet to the garment. Otherwise, opening the press can cause the transfer sheet to lift prematurely.
- For more precise placement, lay the garment out on a table, position the transfer sheet appropriately and tape the corners before placement on the press.

11. Cover the transfer sheet and garment with kraft paper or a Teflon sheet and press the garment at 310°F / 154°C for 25 seconds with high pressure for cotton textiles.

- If you are pressing onto 100% poly, press at 265°F / 129°C.
- If you are pressing onto 50/50 cotton/poly, press at 285°F / 140°C.
- You can perform this step ONLY as low as 250°F / 121°C if necessary to avoid dye migration on polyester fabrics.
- **TIP:** Pressing at a lower temperature in all cases will result in a more vivid final product.

12. Remove the garment from the heat press carefully and immediately lay flat. Allow it to cool for at least 5 minutes.

13. Once the garment is completely cooled, carefully peel away the transfer sheet in one smooth, continuous rolling motion.

- Removal while still warm could lead to an incomplete or faulty transfer.
- It is suggested that you start your pull from an area that has the most toner coverage. The image will adhere to the garment. Perform this step within 60 mins or less.
- **TIP:** If you are encountering resistance when peeling (climate changes can affect this), you can instead use the quick pull method and peel the sheet away 'like a band-aid'; one quick, fast pull.

14. Re-Pressing (AKA post press or fixing press) the image into the garment is required for wash durability.

- Place the textile back on the heat press
- Cover with the included fixing sheet or kraft paper, for a matte finish.



TIP: UniNet recommends re-pressing at a lower temperature to retain the vibrancy of the image. A hotter post press may dull out the pressed image. Repress at 265°F / 129°C for 30 seconds with heavy pressure to increase durability.

- If re-pressing at 310°F / 154°C, do so for only 10 seconds.

15. Wait 15 seconds before removing the fixing or kraft paper to avoid any part of the transfer from sticking to the cover sheet.

- Pull slowly in one smooth, continuous motion. It is important to wait before pulling the paper off, otherwise it could pull the design off the garment!
- While the garment is still on the press and still hot; lightly stretch the material to allow the toner to soak into the fabric to prevent cracking.

TECH TIPS

There are many variables that could produce different results. Specific steps may need to be altered based on:

- **Type of image:** Photos or full-color graphics may require a longer press time than vector images or text.
- **Type of garment:** Cotton, Polyester, Spandex and Lycra material all respond differently to heat. All instructions are based on cotton garments.
- If your presses are not pulling cleanly, preheat the lower platen of the press in the closed position for several minutes to retain the necessary heat to perform this step.
- **Toner Coverage:** Halftones in image may cause undesired results. Toner coverage should not be less than 70% otherwise there may be issues with transferring the adhesive to the transfer sheet. The RIP will add the necessary amount of white to the image to avoid this situation. Those printing outside of the RIP software may encounter issues such as incomplete adhesive transfer.
- **Type and brand of Heat Press:** The temperature and duration varies slightly based on the heat press being used. All instructions are based on using a Hotronix Fusion press (recommended). Clam shell and other types of swing away presses may also yield different results. Always place the transfer media in the middle of your heat press. Some heat presses do not have uniform heat and pressure distribution, which can affect your final project.


Increasing brightness (Non Ultra Bright Product):


For IColor 550/540 owners only: If printing with the IColor 550/540 printer, use up to 280% white coverage for a brighter image. However, using too much white can result in washed out colors. If this is the case, proceed to the next section, 'increasing vibrancy'. Alternatively, use the Ultra Bright version of this paper for more vivid and brighter images.

Increasing vibrancy (Non Ultra Bright Product):

For IColor 550/540 owners only: If a more vivid image is required after using the above suggestions, you can print on the adhesive sheet of the media as well. To print on the adhesive 'B' sheet using the IColor ProRIP software:

- Select the Underprint Queue and DO NOT MIRROR.
- Print mode should be set to 'transparency' and **media setting to 'card stock'**. This method will allow you to add a bit more white (280%) without the washed out look that may occur.

 UNINET does not cover fuser damage if a jam occurs, so pay particular attention to the print settings. Do so at your own risk. Fusers are not covered under warranty.

 Only use the included fixing sheet or kraft paper made for heat press applications! The use of butcher paper, Teflon Sheets or other kinds not specifically designed for heat transfer applications can cause the image to stick to the paper.

During **Step 6** of these instructions, it is important that the adhesive sheet is placed on top because:

- The source of heat is on top and heat is transferred directly to the adhesive sheet instead of passing through the transfer sheet
- When pulling the sheets apart, the sheet on top tends to curl. If that was your transfer sheet, it would then be difficult to place on your garment and could be ruined if the image touched itself while hot.

If, after performing **Step 7**, certain colors appear 'blotchy' or inconsistent, it is recommended to place 2 layers of polyester fabric, a single layer of cotton fabric or a polyester shirt on top of the cover sheet and transfer when pressing to the adhesive. This slows the rate at which the transfer heats up and assists with evening out the pressure when pressing.

During **Step 7**, note that the denser your image, the more difficult it will be to pull the A & B sheets apart. Start out with less dense, weeded or rasterized images to perfect your process. Full coverage images take some skill to successful pull cleanly and may require a longer press time and/or higher temperature. Full coverage tabloid graphics are not recommended.

If, during **Step 8**, your images are not peeling cleanly, first ensure that you are printing the right amount of white over your image.

- If so, then preheat the bottom platen of your heat press to ensure it's hot enough. Cool lower platens are the main cause of inconsistent A/B pulls.
- If this still does not resolve the issue, consult the Humidity and Storage sections on page 4.
- When pressing large areas of black (especially using the IColor 800W), it may be necessary to increase the press time from 120 sec to 200 sec because of heavier than normal toner coverage. Increasing the dwell time before pulling will also help with adhesion.

If, during **Step 11**, you are adjusting the heat press temperature to accommodate delicate material, you must increase the temperature to 310°F / 154°C for **Step 6**. The adhesive will not transfer over properly if set at a lower temperature. Using two heat presses would greatly increase your output and is recommended.

For cotton / poly blend hoodies:

- Press at 250°F / 121°C for 20 seconds, cool immediately and roll the transfer sheet off very tightly.
- Repress for 15 seconds and cool immediately. A lower press temperature and immediate cooling are necessary to prevent dye migration.

If you are seeing stray adhesive sticking to your garment or substrate during the transfer **Step 11** of these instructions, try reducing the press pressure to 'medium' or '5'.

If some of your image isn't sticking to the garment properly during **Step 13**, start your pull from an area that has the most toner coverage. Example, DO NOT start your pull from a dot or a small independent portion of your graphic. The more toner coverage, the higher the probability that you won't lose part of your image when getting started.

On a lower quality press when heat distribution is an issue, you can increase your success rate by using a black piece of cotton fabric over the A/B sheet during step 6, and pressing at 335°F / 168°C for 120 seconds. Make sure to reduce temp when pressing to the garment. Using 2 heat presses would greatly increase your output.

Humidity Suggestions: If your transfers are incomplete (gaps or holes where the adhesive didn't transfer over), then your adhesive media may have been affected by humidity.

Follow these steps to remove the humidity:

- Place the adhesive sheet(s) face up in the heat press while hot.
- Do not press them, just allow to sit for approximately 1 – 2 minutes. Then proceed as normal.

Adhesive sheet storage: To prevent humidity from affecting your media, store in a resealable bag. Adding a silica pack will help to absorb any moisture. Use of a de-humidifier will help reduce excess moisture.

Transfer sheet storage: If the media is sticking together due to static electricity, store in a resealable or anti-static bag. Adding a dryer sheet will help reduce the static. Fan out the media before loading into the printer to ensure proper feeding.

Halftones can be corrected by printing white on top of color (either running the sheet through the printer a second pass, or using the IColor TransferRIP or ProRIP Software to apply a white layer in one pass). This will assist with toner coverage and proper adherence to the garment.

There are many types of coatings and finishes applied to textiles and synthetic fabrics, so make certain adhesion is satisfactory and test for washability or scuff-resistance when applying transfer media to such materials.

It is recommended to wash finished garments inside out in cold or warm water and low agitation. Avoid fabric softener, as it may prematurely degrade the transfer. Tumble dry on low setting - For best results, hang to dry. If ironing is necessary, you must place a piece of kraft paper between the pressed image and the hot iron. Failure to do this will result in a melted transfer.

To see video instructions for IColor Select Transfer Media, visit www.icolorprint.com/video

OPTIONALLY AVAILABLE



IColor SmartCUT Software

Easily print oversized images on letter/A4 sized printers with Uninet's optional IColor SmartCUT software. Use any oversized graphic, and the software will split it in half along the most logical path. You can choose to have it split along dark or light areas, depending on the color garment you will be pressing onto. With this software, you can make 3XL shirts that are not possible with even the most expensive of printing systems because you can gang up as many transfer sheets as you want. For use with IColor 2-Step *Standard* and *Select* Transfer Paper. Trial version available at <https://www.icolorprint.com/support>

ALSO AVAILABLE:

IColor 2-Step *Premium* and *Premium STRETCH* Transfer Paper for light and dark colored garments

IColor 2-Step *Select* Transfer Paper for light and dark colored garments

IColor 2-Step **GLITTER** Adhesive Transfer Paper (for use with IColor 2-Step *Standard* Transfer Paper)

IColor 1-Step **LIGHT** and **SPEED TRANS LIGHT** Transfer Paper for light colored garments

IColor 2-Step **Presto!** Transfer Paper for textiles and hard surfaces

IColor 2-Step **Temporary Tattoo** Transfer Paper

IColor 1-Step **CLASSIC, Premium, WOOD AND LEATHER** and **CERAMIC** Hard Surface Transfer Paper

IColor 1-Step *AqualClear* Transfer Paper

IColor Label Paper (Clear and White) – Letter and Tabloid size

IColor Window Cling Paper (Clear and White) - Banner and cut sheet options

IColor Banner Paper

IColor Magnetic Paper – Letter and Tabloid size

...and more! Contact your dealer for more information.

Your UniNet IColor Dealer:
Specialty Graphics Supply Inc.
www.Specialty-Graphics.com
(888) 330-6172

IColor Transfer Paper Comparison Charts

ICOLOR TEXTILE TRANSFER PAPER

ATTRIBUTE	PREMIUM	PREMIUM STRETCH	STANDARD	SELECT UB	SELECT	PRESTO	LIGHT	SPEEDTRANS LIGHT
PROCESS	2 Step	2 Step	2 Step	2 Step	2 Step	2 Step	1 Step	1 Step
DURABILITY (# of Washes @ 104 °F/40 °C)	Up to 100	Up to 100	50+	50+	50+	50+	15+	15+
DARK TEXTILES (BRILLANCE)	BEST	BEST	BETTER	BEST	GOOD	BETTER	FAIR	FAIR
DELICATE TEXTILES	BEST	BEST	GOOD	GOOD	GOOD	GOOD	NOT RECOMMENDED	NOT RECOMMENDED
STRETCHABILITY	BETTER	BEST	GOOD	BEST	BEST	GOOD	GOOD	GOOD
FINISH	MATTE	MATTE	SEMI GLOSS	MATTE	MATTE	SEMI GLOSS	SATIN	SATIN
PRESS TEMPERATURE (°F/°C)	250°F / 120°C	285°F / 140°C	310°F / 154°C	310°F / 154°C	310°F / 154°C	285°F / 140°C	390°F / 200°C	375°F / 190°C
PRESS TIME	30 + 30 secs	45 + 10 secs	120 + 30 secs	120 + 25 secs	120 + 25 secs	120 + 30 secs	15 secs	10 secs
SOFT HAND	BEST	BEST	GOOD	GOOD	GOOD	GOOD	BETTER	BETTER
COST	\$\$\$	\$\$\$	\$\$	\$\$	\$\$	\$\$	\$	\$

ICOLOR HARD SURFACE TRANSFER PAPER

ATTRIBUTE	PREMIUM	CLASSIC	CERAMICS	WOOD/LEATHER	PRESTO! HARD SURFACE	PRESTO! PAPER/WOOD	AQUACLEAR	TATTOO
PROCESS	1 Step	1 Step	1 Step	1 Step	1 Step	1 Step	1 Step	2 Step
DURABILITY (RESISTANT TO SCRATCHING/CHIPPING)	BEST	BEST	BEST	BEST	BEST	BEST	GOOD	BETTER
COLOR BRILLIANCE	BETTER	BETTER	BETTER	BETTER	BEST	BEST	BETTER	BETTER
METALLIC FINISH	NO	NO	NO	NO	YES	YES	NO	NO
PRESS TEMPERATURE (°F/°C)	300°F / 150°C *	300°F / 150°C *	300°F / 150°C *	300°F / 150°C *	320°F / 160°C *	265°F / 130°C *	N/A	265°F / 130°C
PRESS TIME	60 SECS *	60 SECS *	180 SECS *	60 SECS *	180 SECS *	90 SECS *	N/A	40 SECS
ACRYLIC	YES	YES	YES	YES	YES	NO	YES	YES
METAL	YES	YES	NO	NO	YES	NO	YES	YES
CERAMIC	YES	YES	YES	NO	YES	NO	YES	YES
TILE	YES	YES	YES	NO	YES	NO	YES	YES
GLASS	YES	YES	YES	YES	YES	NO	YES	YES
CRYSTAL	YES	YES	YES	YES	YES	NO	YES	YES
PAPER/WOOD/CARDBOARD	YES	YES	NO	YES	YES	YES	NO	YES
LEATHER	YES	YES	NO	YES	NO	NO	NO	YES
CANDLES	NO	NO	NO	NO	NO	NO	YES	YES
FLESH	NO	NO	NO	NO	NO	NO	NO	YES
COST	\$	\$	\$	\$	\$\$	\$\$	\$\$	\$\$\$

* Temperature and press time varies based on substrate

November 2020 Revision - A newer version of this manual may be available at www.icolorprint.com/support