

HOT OR

COLD HARD CASH



Make \$\$\$ in hard surface decoration with **Versa Sheen**.

AW Specialty Papers LLC

Versa Sheen is a laser-printable, one-step, multi-surface media, that applies at low temps and is super easy to peel. The name comes from its **versatility**, and its **glossy finish**.

"Versa"

"Versa" refers to the product's versatile nature. Due to its outstanding capability with low-temperature applications, Versa Sheen opens the door to decorating many different substrates, including Acrylic, Wood, and more! Additionally, the product can be peeled hot or cold, leading to a more versatile workflow.

"Sheen"

"Sheen" represents the product's professional-looking, glossy finish. To achieve a similar result with other hard surface media, one must both purchase glossy finishing sheets, as well as repress the substrate. Versa Sheen eliminates the need for extra media and cuts waste. This makes your final product both more professional and valuable.

Example Uses:

Drinkware • Hand Mirrors • Ornaments
Mugs • Awards • Name Tags • More...

Surface Applications



Glass



Wood



Ceramic



Acrylic



Metal

And
MORE!

INSTRUCTIONS

for use with
no thermometer

Recommended Print Settings

Printer



Laser

Media Type

"Glossy"
"Labels 2"
"Opaque"

Toner



White Toner
Compatible

Print on



Glossy Side

Metal



Glass



Ceramic



Wood



Acrylic



Peeling

Peel **warm** or **cold**

For best results during a **warm peel**, allow substrate to sit (*off heat source*) for around **10 seconds** before peeling

To place an order, please visit Specialty Graphics Supply Inc.
at www.Specialty-Graphics.com

INSTRUCTIONS

for use with
rapid rise thermometer

Recommended Print Settings

Printer



Laser

Media Type

"Glossy"
"Labels 2"
"Opaque"

Toner



White Toner
Compatible

Print on



Glossy Side

Metal

set press temp. to 390°F

open press at 310°F

pressure HEAVY

Glass

set press temp. to 390°F

open press at 310°F

pressure HEAVY

Ceramic

set press temp. to 390°F

open press at 310°F

pressure HEAVY

Wood

set press temp. to 390°F

open press at 310°F

pressure HEAVY

Acrylic

set press temp. to 390°F

open press at 310°F

pressure HEAVY

Peeling

Peel **warm** or **cold**

For best results during a **warm peel**, allow substrate to sit (*off heat source*) for around **10 seconds** before peeling

To place an order, please visit Specialty Graphics Supply Inc.
at www.Specialty-Graphics.com